

GENEVA

Electric unvented water heater
with basic control

CHARACTERISTICS

- External thermal regulator
- External water temperature indicator
- Exclusive thermal break system helping reduce heat loss
- Tank: 5 years guarantee
- Electronics: 2 years guarantee



Energy classification **C**

WATER HEATING

PRODUCT INFORMATION

MODELS	GW1050DHW4	GW1080DHW4	GW1100DHW4
Volume (L)	50	80	100
Load profile	M	L	L
Nominal power (W)	1,500	1,500	1,500
DIMENSIONS			
Diameter x height (mm)	440 x 597	440 x 847	440 x 987
Installed depth (mm)	490	490	490
Distance between connections (mm)	110	110	110
MECHANICAL CHARACTERISTICS			
Empty weight (kg)	15.7	21.4	24.0
Water connections (")	1/2"	1/2"	1/2"
Finishes	White RAL 9016		
TRADE PRICE	£ 196	£ 229	£ 250

TECHNICAL INFORMATION

Copper heating elements	✓
Vitrified steel tank	✓
Magnesium protective anode	✓
CFC-free polyurethane foam insulation	✓
Basic control panel made of PP	✓
Operation indicator light	✓
Maximum working pressure	8
Protection Grade	IP22
Energy classification	C

INSTALLATION

Installation position	Vertical
Safety valve	✓
Installation kit required (sold separately)	✓
Optional support accessories available	✓

FUNCTIONS

External mechanical temperature control	✓
---	---


SECURITY

Safety thermostat	✓
-------------------	---

REGULATIONS & GUARANTEES

2004/108/CE EMC Directive	✓
2006/95/CE LVD Directive	✓
Guarantee on tank	5 years
Guarantee on electronics	2 years

DIAGRAMS



WATER HEATING

2
YEARS
GUARANTEE
ON PRODUCT

ROME, SIENA & GENEVA INSTALLATION KIT

It is **mandatory** for all models of unvented domestic hot water heaters to be installed with an installation kit. This kit is composed of:



Pressure reducing & relief valve




Tundish



Expansion vessel



MODELS	KITKW02
Compatible with	50 - 150 L
CHARACTERISTICS	
Expansion vessel	12 litres (0.1 Mpa)
Tundish	15 - 25 mm
Pressure reducing valve	0.35 Mpa
Relief valve	0.60 Mpa
TRADE PRICE	£ 152



DETAILS OF THE INSTALLATION

- 1 Mains cold water supply
- 2 Stop cock (not supplied)
- 3 Pressure reducing valve (included)
- 4-5 Check valve - Expansion relief valve (included)
- 6 Discharge pipe 22 mm
- 7 Drain cock (not supplied)
- 8 Tundish (included)
- 9 Expansion vessel (included)
- 10 T/P relief valve (included)
- 11 Electrolytic fittings (included)

* This image is only for reference. Check the instruction manual or the Building Regulations (PART G) for specific details and accessories required to perform a proper installation. The Rointe water heaters must be installed by an installer with a valid Unvented Water Heaters Installer certification.