

**Product Code:** PSPBFB

**Description:** Powersaver Plus Electronic Fused Boost Controller with Single Button Operation in Black



| General Information                |  | Outputs  |   |
|------------------------------------|--|--|---|
| Dimensions (mm)                    | 86 x 86 x 35                                 | Switched Output                                    | 230V AC, Double Pole; Fused 13A Resistive (3kW) |
| Flush Mounting Back Box Depth (mm) | 25   | Maximum LED Lamp Load Rating (W)                   | 200 @ 230V                                      |
| Finish                             | Black  | Maximum Incandescent, Halogen Lamp Load Rating (W) | 1000  |
| Materials                          | ABS  | Maximum Fluorescent Lamp Load Rating (W)           | 500   |
| Mounting                           | Single Pattress – Surface and Flush Mounting | Maximum Fluorescent Lamp Load Rating (W)           | 500   |
| Warranty (Years)                   | 3  |  |   |
| Programming                        |  |  |   |
| Selectable Boost Durations         | 30 Minutes, 1 Hour or 2 Hours                |  |   |
| Supply & Power                     |  |  |   |
| Supply Voltage (V AC)              | 230  |  |   |
| Frequency (Hz)                     | 50   |  |   |
| Fuse Fitted (BS1362)               | 13A  |  |   |
| Environment                        |  |  |   |
| Ingress Protection                 | IP20   |  |   |
| Operating Temperature (°C)         | -10 to +40                                   |  |   |
| Temperature Rating                 | T40  |  |   |
| <b>Standards</b>                   | BS EN 60730                                  |  |   |
| <b>Supplied</b>                    | BS1362 13A Fuse                              |  |   |