

**Product Code:** PSPBFS

**Description:** Powersaver Plus Electronic Fused Boost Controller with Single Button Operation in Silver



### General Information

|                                    |  |
|------------------------------------|--|
| Dimensions (mm)                    | 86 x 86 x 35                                 |
| Flush Mounting Back Box Depth (mm) | 25   |
| Finish                             | Silver                                       |
| Materials                          | ABS  |
| Mounting                           | Single Pattress – Surface and Flush Mounting |
| Warranty (Years)                   | 3  |

### Programming

Selectable Boost Durations | 30 Minutes, 1 Hour or 2 Hours

### Supply & Power

|                       |     |
|-----------------------|-----|
| Supply Voltage (V AC) | 230 |
| Frequency (Hz)        | 50  |
| Fuse Fitted (BS1362)  | 13A |

### Environment

|                            |            |
|----------------------------|------------|
| Ingress Protection         | IP20       |
| Operating Temperature (°C) | -10 to +40 |
| Temperature Rating         | T40        |

**Standards** BS EN 60730

**Supplied** BS1362 13A Fuse

### Outputs

|  |   |
|--|---|
| Switched Output                                    | 230V AC, Double Pole; Fused 13A Resistive (3kW) |
| Maximum LED Lamp Load Rating (W)                   | 200 @ 230V                                      |
| Maximum Incandescent, Halogen Lamp Load Rating (W) | 1000  |
| Maximum Fluorescent Lamp Load Rating (W)           | 500   |
| Maximum Fluorescent Lamp Load Rating (W)           | 500   |