

Product Code: PPSF247

Description: Powersaver Plus Electronic 24/7 Fused Boost controller with Programmable Operations



General Information

Dimensions	86mm x 86mm x 35mm 12mm Depth (Without Back Box)
Display	LCD, Clear Indication Display

Power

Operating Voltage	230V AC, 50Hz
IEC Protection Class	Class II

Construction

Material	ABS
Fixing	Surface and Flush Mounting

Outputs

230VAC	Double Pole; Fused 13A Resistive (3kW)
Flush Mounting	Minimum 25mm Depth
Incandescent, Halogen lighting	750W
Fluorescent Lighting	500W
LED Lighting	200W
Compact Fluorescent Lighting	100W
Fuse	BS1362 13A Fuse

Programming

Programming Schedule	24 Hour, 5/2 Day & 7 Day
Available Operations	Up to 10 per Day
Summer/Winter Time Change	Yes; Automatic
Memory Reserve	Permanent reserve setting
Button Lock	Yes

Boosts

Selectable Durations	15 minutes, 30 minutes, 1 hour, 2 hours, 4 hours, or 6 hours
-----------------------------	--

Environment

Ingress Protection	IP20
Temperature Rating	T40
Operating Temperature	0°C to 40°C

Component Supplied

BS1362 13A Fuse