

**Product Code:** PSPSF24B

**Description:** Powersaver Plus Electronic 24 Hour Fused Boost controller with Programmable Operations in Black



General Information		Outputs	
Dimensions (mm)	86 x 86 x 35	Switched Output	230V AC, Double Pole; Fused 13A Resistive (3kW)
Flush Mounting Back Box Depth (mm)	25	Maximum LED Lamp Load Rating (W)	200 @ 230V
Finish	Black	Maximum Incandescent, Halogen Lamp Load Rating (W)	750
Display	LCD, Clear Indication Display	Maximum Fluorescent Lamp Load Rating (W)	500
Materials	ABS	Maximum Fluorescent Lamp Load Rating (W)	500
Mounting	Surface and Flush Mounting		
Warranty (Years)	3		
Programming			
Programming Schedule	24 Hour		
Available Operations	Up to 10 per Day		
Summer/Winter Time Change	Yes (Automatic)		
Memory Reserve	Permanent Reserve Setting		
Button Lock	Yes		
Selectable Boost Durations	15 Minutes, 30 Minutes, 1 Hour, 2 Hours, 4 Hours, or 6 Hours		
Supply & Power			
Supply Voltage (V AC)	230		
Frequency (Hz)	50		
Fuse Fitted (BS1362)	13A		
Environment			
Ingress Protection	IP20		
Operating Temperature (°C)	0 to +40		
Temperature Rating	T40		
<b>Standards</b>	BS EN 60730		
<b>Supplied</b>	BS1362 13A Fuse		